

Product Data Sheet**Product: 43# Coated Thermal Transfer W/Barrier Tire + 50# liner****Item #: 1005**

Face Stock: A coated thermal transfer paper that provides excellent barcode and other print applications. The lamination of a polyester barrier provides additional strength to the paper and protection to the finish label from chemical migration on various substrates.

Caliper: .0043" +/- 10%

Face Stock Properties

Parameter	Unit of Measure	Value
Tearing Strength MD	grams	39
Tearing Strength CD	grams	50
Basis Weight	pounds/ream	61

Adhesive: Tire label adhesive is a very aggressive adhesive designed for hard to label substrates such as tires, recycled corrugated packaging, fabrics and other rough surfaces.

Caliper: .002"

Minimum Temperature: 45°F

Service Temperature Range: -20° F - +160° F

Tack: 126 oz/in²



Liner: 50# is a moisture-stabilized 3.2mil bleached super calendered kraft paper stock, offering excellent die cutting and matrix stripping.

Shelf life: 1 year stored at 72°F and 50% RH

Construction Caliper: .0095" +/- 10%

Published data is based on tests and believed to be reliable but does not constitute a guarantee or warranty. As with all label applications, this product should be thoroughly tested under end-use conditions to ensure it meets the requirements of the application.