



# Performance Guide

Represents Typical Values Only

**2Mil Clear PET PT AP1 50#**

**Item # C1000**

## FACE

2Mil Clear Polyester film label stock designed for a wide variety of label applications. This film has been corona treated to enhance printability across many printing processes. The polyester film provides excellent tear strength, heat resistance, dimensional stability, and chemical resistance.

Caliper: .002" +/- 10%

## ADHESIVE

AP1 is an aggressive general purpose hot melt adhesive with good die cutting and mandrel hold. AP1 works well on corrugated, HSE and LSE plastics and other packaging surfaces. Good low temperature properties.

Caliper: .0008"

Min. Application Temperature: -10°F

Service Temperature Range: -40° - 140° F

Loop Tack: 9.25

180 Peel: 4.9

SAFT: 181

## LINER

A 50# liner (3.1mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0031" +/- 10%

Basis Weight: 50#

## CONSTRUCTION CALIPER

.006" +/- 10%

**Shelf life: 1 year stored at 72°F and 50% RH**

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

**Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839**

**800-813-8907**

[www.paperresources.com](http://www.paperresources.com)