



Performance Guide

Represents Typical Values Only

Red Fluorescent AP1 40#

Item # C1002

FACE

60# matte, neon bright alkaline sheet designed for high visibility and impact printing.

Caliper: .0038" +/- 10%

Tensile MD: 35 lbs/inch

Tensile TD: 15 lbs/inch

Tearing MD: 55 grams

Tearing TD: 60 grams

ADHESIVE

AP1 is an aggressive general purpose hot melt adhesive with good die cutting and mandrel hold. AP1 works well on corrugated, HSE and LSE plastics and other packaging surfaces. Good low temperature properties.

Caliper: .0008"

Min. Application Temperature: -10°F

Service Temperature Range: -40° - 140° F

Loop Tack: 9.25

180 Peel: 4.9

SAFT: 181

LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%

Basis Weight: 40#

CONSTRUCTION CALIPER

.007" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com