



Performance Guide

Represents Typical Values Only

50# Coated Thermal Transfer CrocLock HCWT 40#

Item # C1013

FACE

50# premium coated thermal transfer face sheet. A matte print receptive coating is specifically designed for excellent thermal transfer printability.

Caliper: .0031" +/- 10%

ADHESIVE

CrocLock is an aggressive hot melt adhesive designed for difficult to label substrates. Key attributes include excellent on press convertibility as well as quick tack properties. Designed for use on wood, texture surfaces, plastics, corrugated and other hard to label surfaces.

Caliper: 0.0012

Min. Application Temperature: 30°F

Service Temperature Range: -40° to +145° F

Loop Tack ATSM D-6195

Stainless steel #/inch: 6.0lbs

Peel Adhesion 180 10 minutes /	Stainless	HDPE	Corrugated	Wood	Powder Coat
24 hours / lbs per lineal inch:	6.0/6.0	3.0/3.5	1.5/2.5	3.5/3.5	5.5/6.8
Shear :	7000	ASTM D-3654 Shear (minutes) 1" X 1" X 1000 grams			



LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%

Basis Weight: 40#

CONSTRUCTION CALIPER .0067" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com