



Performance Guide

Represents Typical Values Only

60# Semigloss CrocLock E HCW 40#

Item # C1015E

FACE

A premium coated semigloss paper that provides excellent printing characteristics using flexo, offset or letterpress.

Caliper: .0031" +/- 10% Gloss: 70
 Brightness: 89 Opacity: 87.5

ADHESIVE

CrocLock E is an aggressive hot melt adhesive designed for difficult to label surfaces. This adhesive has excellent tack and peel properties at a wide range of temperatures. Excellent adhesion to corrugated and other packaging materials when moisture, dirt and debris may be present on the application surface.

Caliper: 0.0012

Min. Application Temperature: 30°F

Service Temperature Range: -50° to +185° F

Loop Tack ATSM D-6195 Stainless steel #/inch: 6 lbs



Peel Adhesion 180 10 minutes / 24 hours / lbs per lineal inch:	Stainless	HDPE	Corrugated	Wood	Powder Coat
	6.5/6.7	4.0/4.5	3.5/4.0	3.5/4.0	6.5/6.5
Shear :	7000	ASTM D-3654 Shear (minutes) 1" X 1" X 1000 grams			

LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%
 Basis Weight: 40#

CONSTRUCTION CALIPER

.0067" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com