



# Performance Guide

Represents Typical Values Only

**60# High Gloss Opaque CrocLock HCW 40#**

**Item # C1017**

**FACE** 60# cast coated, high gloss paper with a black barrier applied to the backside of the paper for an added opacity, where blackout to underlying images or print is required. The glossy finish allows for a wide variety of printing applications.

Caliper: .0039" +/- 10%	Tearing MD: 55 grams
Brightness: 75	Tearing CD: 60 grams
Basis Weight: 60# / 3300	Tensile MD: 30#/inch
Opacity: >95%	Tensile CD: 19#/inch

**ADHESIVE** CrocLock is an aggressive hot melt adhesive designed for difficult to label substrates. Key attributes include excellent on press convertibility as well as quick tack properties. Designed for use on wood, texture surfaces, plastics, corrugated and other hard to label surfaces.

Caliper: 0.0012  
 Min. Application Temperature: 30°F  
 Service Temperature Range: -40° to +145° F  
 Loop Tack ATSM D-6195 Stainless  
 steel #/inch: 6.0lbs



Peel Adhesion 180 10 minutes / 24 hours / lbs per lineal inch:	Stainless	HDPE	Corrugated	Wood	Powder Coat
	6.5/6.7	4.0/4.5	3.5/4.0	3.5/4.0	6.5/6.5

SAFT: 140 Shear : 7000 ASTM D-3654 Shear (minutes) 1" X 1" X 1000 grams

**LINER** A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%  
 Basis Weight: 40#

**CONSTRUCTION CALIPER** .0075" +/- 10%

**Shelf life: 1 year stored at 72°F and 50% RH**

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

**Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839**

**800-813-8907**

[www.paperresources.com](http://www.paperresources.com)

