



Performance Guide

Represents Typical Values Only

1.5Mil Clear PET STC SnappLock 40#

Item # C1038L

FACE

1.5mil Clear PET face stock with a release coating on 1 side designed to offer a consistent long term release surface for various adhesive constructions.

Caliper: .0015" +/- 10%

ADHESIVE

SnappLock is an aggressive hot melt adhesive featuring high initial tack, high peel values and good temperature resistance. Excellent die cutting adhesive allowing for higher converting speeds. Designed for use on plastic, corrugated, steel, low surface energy plastics as well as other hard to label surfaces. Good internal strength allows SnappLock to perform well in cylindrical applications.

Caliper: 0.001

Min. Application Temperature: 40°F

Service Temperature Range: -40° to +190° F

Loop Tack Stainless Steel (lbf) 11

Peel Adhesion 180 10 minutes / 24 hours / lbs per lineal inch:	Stainless	HDPE	Corrugated	Wood	Powder Coat
Shear :	6.0/7.0	5.1/6.5	n/a	.9/.9	n/a

LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024

CONSTRUCTION CALIPER

.0049" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com