



Performance Guide

Represents Typical Values Only

2Mil Clear Polypropylene ITC CrocLock HCW 40#

Item # C1066

FACE

A 2mil transparent, top coated, biaxially oriented polypropylene film. This film has a top coating suitable for printing on HP digital presses and a shelf life of 1 year.

Caliper: .002" +/- 10%	Elongation % MD: 180
Basis Weight: 28.8lbs/ream	Elongation % CD: 55
Surface Tension: 42	Tensile MD: 20,000psi
	Tensile CD: 35,000psi

ADHESIVE

CrocLock is an aggressive hot melt adhesive designed for difficult to label substrates. Key attributes include excellent on press convertibility as well as quick tack properties. Designed for use on wood, texture surfaces, plastics, corrugated and other hard to label surfaces.

Caliper: 0.0014
 Min. Application Temperature: 30°F
 Service Temperature Range: -40° to +145° F
 Loop Tack ATSM D-6195 Stainless
 steel #/inch: 6lbs



	Stainless	HDPE	Corrugated	Wood	Powder Coat
Peel Adhesion 180 10 minutes / 24 hours / lbs per lineal inch:	6.5/6.7	4.0/4.5	3.5/4.0	3.5/4.0	6.5/6.5
Shear :	3100	ASTM D-3654 Shear (minutes) 1" X 1" X 1000 grams			

LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%
 Basis Weight: 40#

CONSTRUCTION CALIPER .0059" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com