



Performance Guide

Represents Typical Values Only

8Mil Matte White Synthetic TT AP1 50#

Item # C1076

FACE 8Mil matte finish, white opaque, mineral-reinforced polypropylene printing and converting film. This product has an excellent combination of strength, rigidity, and yield. It is an excellent candidate for a wide range of applications where durability, strength, moisture, chemical resistance, and superior printability is required.

Caliper: .008" +/- 10% Tear Strength (grm/mm): MD3000 / TD5500
Yield (lbs/sq. in.): 3066 Elongation at Break(%): MD550 / TD500
Tensile Strength (PSI): MD3000 / TD2000 Surface Tension(Dynes/sq.cm.): 44

ADHESIVE AP1 is an aggressive general purpose hot melt adhesive with good die cutting and mandrel hold. AP1 works well on corrugated, HSE and LSE plastics and other packaging surfaces. Good low temperature properties.

Caliper: 0.00087
Min. Application Temperature: -10°F
Service Temperature Range: -40° - +140° F
Loop Tack: 9.25
180 Peel: 4.9
SAFT: 181

LINER A 50# liner (3.1mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0031" +/- 10%
Basis Weight: 50#

CONSTRUCTION CALIPER .012" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com