



# Performance Guide

Represents Typical Values Only

**54# SEMIGLOSS TE OSB 40#**

**Item # C1077**

## FACE

This Semigloss sheet features premium brightness and enhanced blue-white shade and high opacity. Designed for high end labels and excellent for flexographic printing. This sheet has high strength allowing for high speed matrix stripping.

Caliper: .0027" +/- 10%  
Opacity: 87%  
Gloss: 72%  
Brightness: 89%

## ADHESIVE

OSB adhesive is a very aggressive adhesive designed for hard to label substrates such as wood, recycled corrugated packaging, fabrics, textured plastics and other rough surfaces.

Caliper: 0.001" +/-10%  
Min. Application Temperature: 10F  
Service Temperature Range: -60° - 145° F  
Loop Tack: 6  
180 Peel: 5      SAFT: 160

## LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%  
Basis Weight: 40#

## CONSTRUCTION CALIPER

.0062" +/- 10%

**Shelf life: 1 year stored at 72°F and 50% RH**

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

**Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839**

**800-813-8907**

[www.paperresources.com](http://www.paperresources.com)