



Performance Guide

Represents Typical Values Only

3Mil Matte White Polypropylene TT OSB 40#

Item: C1089

FACE

3Mil White Film, mineral-filled, biaxially oriented polypropylene is designed for applications requiring strength and durability. A matte print receptive coating is specifically designed for excellent thermal transfer printability.

Caliper: .003" +/- 10%

ADHESIVE

OSB adhesive is a very aggressive adhesive designed for hard to label substrates such as wood, recycled corrugated packaging, fabrics, textured plastics and other rough surfaces.

Caliper: 0.001

Min. Application Temperature: 10°F

Basis Weight: .0014

Service Temperature Range: -60° to +145° F

Loop Tack ATSM D-6195 Stainless steel #/inch: 6.0lbs

Peel Adhesion 180 10 minutes / 24 hours / lbs per lineal inch:	Stainless	HDPE	Corrugated	Wood	Powder Coat
	6.5/6.7	4.0/4.5	3.5/4.0	3.5/4.0	6.5/6.5

Shear : 3100 ASTM D-3654 Shear (minutes) 1" X 1" X 1000 grams



LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%

Basis Weight: 40#

CONSTRUCTION CALIPER

.0064" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com