



Performance Guide

Represents Typical Values Only

3.2Mil Matte White PE OSB C 40#

Item # C1117+

FACE

Polyolefin-based, clay coated film designed to be compatible with most print methods. This product provides superior performance where resistance to tear, grease, moisture, and temperature fluctuation is needed. This polyolefin will die cut and fold easily as well as being compatible with hot stamping and embossing. Outdoor durability will last up to 18 months depending on the climate and exposure. When using for hand applied applications it is recommended to remove the liner from the label in order to reduce pickers curl.

Caliper: .0032" +/-10%

ADHESIVE

OSB adhesive is a very aggressive adhesive designed for hard to label substrates such as wood, recycled corrugated packaging, fabrics, textured plastics and other rough surfaces.

Basis Weight: .003

Caliper: 0.0022" +/-10%

Min. Application Temperature: 10°F

Service Temperature Range: -60° - 145° F

Loop Tack: 6

Peel: 5 SAFT: 160

LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%

Basis Weight: 40#

CONSTRUCTION CALIPER .0086" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com