



Performance Guide

Represents Typical Values Only

54# Semigloss Opaque SnappLock 40#

Item # C1135

FACE

A C1S paper designed for flexographic and TT printing. This product will delaminate easily, showing evidence of tampering when combined with an aggressive adhesive. Features premium brightness and enhanced blue-white shade with an opaque black barrier on the adhesive side. Testing is recommended for compatibility with TT ribbons.

Caliper: .0031" +/-10%

Basis Weight: 50 lbs/ream

ADHESIVE

SnappLock is an aggressive hot melt adhesive featuring high initial tack, high peel values and good temperature resistance. Excellent die cutting adhesive allowing for higher converting speeds. Designed for use on plastic, corrugated, steel, low surface energy plastics as well as other hard to label surfaces. Good internal strength allows SnappLock to perform well in cylindrical applications.

Caliper: 0.0014" +/-10%

Min. Application Temperature: 40F

Service Temperature Range: -40° - 190° F

Loop Tack: 11.3

180 Peel: 7.2

SAFT: 160

LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%

Basis Weight: 40#

CONSTRUCTION CALIPER

.0069" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com