



# Performance Guide

Represents Typical Values Only

Direct Thermal TC Tire 40#

Item # C1147

**FACE** A topcoated, 190-sensitivity, thermal label face stock designed for use in standard speed printers. Product provides good environmental resistance and high bar code scan rates.

Caliper: .00315 3.15" +/- 0.25/80 +/- 7

**ADHESIVE** Tire label adhesive is an aggressive hot melt rubber based adhesive designed for hard to label substrates such as tires, recycled corrugated packaging, fabrics and other rough surfaces.

Caliper: 0.0022

Min. Application Temperature: 10°F

Service Temperature Range: -60° to +145° F

Loop Tack: 6.0lb/in

180 Peel: 5.0lb/in

SAFT: 160

**LINER** A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%

Basis Weight: 40#

**CONSTRUCTION CALIPER** .0077" +/- 10%

**Shelf life: 1 year stored at 72°F and 50% RH**

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

**Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839**

**800-813-8907**

[www.paperresources.com](http://www.paperresources.com)