



Performance Guide

Represents Typical Values Only

50# Coated TT OSB+ 40#

Item # C1153

FACE

50# premium coated thermal transfer face sheet. A matte print receptive coating is specifically designed for excellent thermal transfer printability.

Caliper: .0035 +/- 10%

Opacity: 90%

Density: .79g/cm

Tearing MD: 560lbs/in

Tearing CD: 640lbs/in

ADHESIVE

OSB+ is a heavy coat weight hot melt adhesive designed to perform well on difficult to label substrates. This adhesive has had success adhering to wood, tires, carpet back, textured plastics and recycled corrugated. OSB+ has performed well on cold, wet surfaces that have dust/debris present.

Caliper: 0.0018

Min. Application Temperature: 10°F

Service Temperature Range: -60° to +145° F

Loop Tack: 6.0lb/in

180 Peel: 5lb/in

SAFT: 160

LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%

Basis Weight: 40#

CONSTRUCTION CALIPER .0077" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com