



# Performance Guide

Represents Typical Values Only

**60# Saturated Litho Tire 40#**

**Item # C1175**

## FACE

This face stock is a 60# Saturated Latex impregnated paper that is coated for flexographic printing. 60# Saturated litho has good weather resistance and conforms well to uneven surfaces.

Caliper: .0032" +/- 10%

Tensile MD: 25 lbs/inch

Tensile CD: 17 lbs/inch

Tearing MD: 55 grams

Tearing CD: 58 grams

## ADHESIVE

Tire label adhesive is a very aggressive adhesive designed for hard to label substrates such as tires, recycled corrugated packaging, fabrics and other rough surfaces.

Caliper: 0.0014" +/-10%

Min. Application Temperature: 10°F

Service Temperature Range: -60° - 145° F

Loop Tack: 6

180 Peel: 5

SAFT: 160

## LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%

Basis Weight: 40#

## CONSTRUCTION CALIPER

.007" +/- 10%

**Shelf life: 1 year stored at 72°F and 50% RH**

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

**Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839**

**800-813-8907**

[www.paperresources.com](http://www.paperresources.com)