



Performance Guide

Represents Typical Values Only

3.2MIL MATTE WHT PE OSB+ 4.6Mil Liner

Item # C1177

FACE

Polyolefin-based, clay coated film designed to be compatible with most print methods. This product provides superior performance where tear resistance, grease resistance, waterproof, and resistance to temperature fluctuation is needed. This polyolefin will die cut and fold easily as well as being compatible with hot stamping and embossing. Outdoor durability will last up to 18 months depending on the climate and exposure. When using in hand applied applications it is recommended to remove the liner from the label in order to reduce pickers curl.

Caliper: .0032" +/-10%

ADHESIVE

OSB+ is a heavy coat weight hot melt adhesive designed to perform well on difficult to label substrates. This adhesive has had success adhering to wood, tires, carpet back, textured plastics and recycled corrugated. OSB+ has performed well on cold, wet surfaces that have dust/debris present.

Caliper: 0.0018" +/-10%

Min. Application Temperature: +10 F

Service Temperature Range: -60° - 145° F

Loop Tack: 6lb/in

SAFT: 160

180 Peel: 5lb/in

LINER

77# silicone coated release liner designed label converting. Supercalendered, clay coated on silicone side. Provides good lay flat properties

Caliper: .0046" +/- 10%

Basis Weight: 77#

CONSTRUCTION CALIPER

.0096" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com