



# Performance Guide

Represents Typical Values Only

**3.8MIL MATTE WHT PE SNAPPLOCK 50#**

**Item # C1191**

## FACE

A polyolefin-based clay coated film product. This provides superior performance, wear and tear resistance, grease resistance, is waterproof and has resistance to temperature fluctuations. This polyolefin will easily die cut and is compatible with hot stamping and embossing. There is an outdoor durability of 18 months, depending on the climate and exposure.

Caliper: .0038" +/-10%

## ADHESIVE

SnappLock is an aggressive hot melt adhesive featuring high initial tack, high peel values and good temperature resistance. Excellent die cutting adhesive allowing for higher converting speeds. Designed for use on plastic, corrugated, steel, low surface energy plastics as well as other hard to label surfaces. Good internal strength allows SnappLock to perform well in cylindrical applications.

Caliper: 0.0012+

Min. Application Temperature: 40°F

Service Temperature Range: -40° to +190° F

180 Peel: 7.2

Loop Tack Stainless Steel (lbf) 11.3

Peel Adhesion 180 10 minutes / 24 hours / lbs per lineal inch:	Stainless	HDPE	Corrugated	Wood	Powder Coat
	6.7/7.3	5.4/6.9	n/a	.9/.9	n/a

Shear : n/a

## LINER

A 50# liner (3.1mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0031" +/- 10%

Basis Weight: 50#

## CONSTRUCTION CALIPER .0081" +/- 10%

**Shelf life: 1 year stored at 72°F and 50% RH**

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

**Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839**

**800-813-8907**

[www.paperresources.com](http://www.paperresources.com)