



Performance Guide

Represents Typical Values Only

Secure Thermal Transfer HP4 40#

Item # C1192

FACE

This matte coated sheet is designed for flexographic and thermal transfer printing. When coated with our HP4 adhesive, this product will delaminate when removal is attempted creating a tamper indicating seal. C1192 is designed to provide a tamper indicating label on surfaces where standard products can be removed without label tear or destruction of the application surface.

Caliper: .0028" +/- 10%	CD Tensile: lbs/in	17
Smoothness: 2.20	N/15mm	45
Gloss: 72%	MD Tear: grams	42
Brightness: 86%	mN	412

ADHESIVE

HP4 is a high peel, high tack, high SAFT adhesive. Our internal testing showed it works submerged in salt water. Because of high molecular weight it has worked in an autoclave application. It has been used as battery label

Caliper: 0.001" +/-10%
Min. Application Temperature: 35F
Service Temperature Range: -20° - +220° F
Loop Tack Stainless Steel (lbf): 9.5
180 Peel: 7.5
SAFT: 190



LINER

A 40# liner bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%
Basis Weight: 40#

CONSTRUCTION CALIPER .0062" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com