



# Performance Guide

Represents Typical Values Only

**60# Semigloss AP2 C 50#**

**Item # C1193**

## FACE

A premium coated semigloss paper that provides excellent printing characteristics using flexo, offset or letterpress.

Caliper: .0031" +/- 10%  
Brightness: 89

Gloss: 70  
Opacity: 87.5

## ADHESIVE

AP2 is an aggressive quick tack adhesive designed to adhere to various surfaces including corrugated, plastics, packaging materials and low surface energy surfaces. This adhesive has been used in BS5609 applications and has good converting properties.

Caliper: 0.0022

Min. Application Temperature: 10°F

Service Temperature Range: -20° to +120° F

Loop Tack: 7

SAFT: 147

180 Peel: 5.75lbs

## LINER

A 50# liner (3.1mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0031" +/- 10%  
Basis Weight: 50#

**CONSTRUCTION CALIPER** .0085" +/- 10%

**Shelf life: 1 year stored at 72°F and 50% RH**

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

**Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839**

**800-813-8907**

[www.paperresources.com](http://www.paperresources.com)