



# Performance Guide

Represents Typical Values Only

2.6Mil White PP TC AP2 40#

Item # C1197

## FACE

A white gloss biaxially oriented polypropylene film top coated for ink receptivity. Features include high opacity, excellent hot/cold moisture resistance, semi-squeeze performance, high stiffness for excellent convertability. Top Coating is print receptive to various methods including TT, Hot Stamp, Water & UV Flexo, Gravure and UV Ink Jet. Testing is recommended to verify print receptivity.

Caliper: .0026" +/- 10%

Opacity: 89%

Tensile Strength psi: 13,000 MD

Tensile Strength psi: 20,000 TD

## ADHESIVE

AP2 is an aggressive quick tack adhesive designed to adhere to various surfaces including corrugated, plastics, packaging materials and low surface energy surfaces. This adhesive has been used in BS5609 applications and has good converting properties.

Caliper: 0.001" +/-10%

Min. Application Temperature: 10°F

Service Temperature Range: -20° to +120° F

Loop Tack: 7

SAFT: 147

180 Peel: 5.75lbs

## LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%

Basis Weight: 40#

**CONSTRUCTION CALIPER** .006" +/- 10%

**Shelf life: 1 year stored at 72°F and 50% RH**

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

**Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839**

**800-813-8907**

[www.paperresources.com](http://www.paperresources.com)