



Performance Guide

Represents Typical Values Only

4MIL WHITE DURABLE PE CROCLOCK 40# DRY EDGE

Item # C1114 DRY EDGE

FACE

4Mil white durable PE based film that performs well in demanding environments. Excellent cold temperature performance, tear resistance and good hole strength. Recommended printing includes flexographic and thermal transfer.

Caliper: .004" +/- 10%

ADHESIVE

CrocLock is an aggressive hot melt adhesive designed for difficult to label substrates. Key attributes include excellent on press convertibility as well as quick tack properties. Designed for use on wood, texture surfaces, plastics, corrugated and other hard to label surfaces.

Coat Weight: .0012

Min. Application Temperature: 30°F

Service Temperature Range: -40° to +145° F

Loop Tack ATSM D-6195 Stainless steel #/inch: 6lbs

Peel Adhesion 180 10 minutes / 24 hours / lbs per lineal inch:	Stainless	HDPE	Corrugated	Wood	Powder Coat
	6.5/6.7	4.0/4.5	3.5/4.0	3.5/4.0	6.5/6.5

Shear : 3100

ASTM D-3654 Shear (minutes) 1" X 1" X 1000 grams

SAFT: 140



LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%

Basis Weight: 40#

CONSTRUCTION CALIPER

.0076" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com