



Performance Guide

Represents Typical Values Only

7PT C1S THERMAL TRANSFER TAG

D1032

FACE

7PT thermal transfer tag with a premium matte coating designed for high quality flexographic and thermal transfer printing. Excellent "lay flat" characteristics.

| | | |
|--------------------|--------------|-------------|
| Caliper: | .007" +/-10% | |
| Basis Weight: | 119lb | TAPPI T 410 |
| Brightness: | 88% | TAPPI T 452 |
| Moisture: | 4.80% | TAPPI T 412 |
| 75 degree gloss: | 26% | TAPPI T 480 |
| Parker Smoothness: | 1.5 PPSU | TAPPI T 555 |

| | | |
|------------------|-----------------|-------------|
| RS MD Stiffness: | 1370 mgf | TAPPI T 543 |
| RS CD Stiffness: | 1370 mgf | TAPPI T 543 |
| RS MD Tensile: | 60 lbs/in | TAPPI T 494 |
| RS CD Tensile: | 30 lbs/in | TAPPI T 494 |
| RS MD Tear: | 145 grams-force | TAPPI T 414 |
| RS CD Tear: | 150 grams-force | TAPPI T 414 |

Common uses: Tickets and Tags

CONSTRUCTION CALIPER .007" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com