



Performance Guide

Represents Typical Values Only

2MIL MATTE WHT PET LSR HP1 1.5MIL HP1+ 50#

Item # C1164

FACE

2mil matte white pet face stock with a laser printable top-coat. Excellent tear strength, heat resistance, opacity, dimensional stability and chemical resistance

Caliper: .002" +/- 10%

ADHESIVE

HP1 adhesive is a high tack, high performance hot melt rubber based adhesive engineered to provide high adhesion while maintaining resistance to severe environments including exposure to petroleum based oils, grease, organic solvents and high humidity. HP1 also provides a high level of performance on LSE plastics including HDPE and adheres well to powder coated surfaces.

Caliper: 0.008" +/-10%
Soft: 195°F

Min. Application Temperature: 40°F
Service Temperature Range: -40° to 200° F

Release Liner

1.5mil Clear PET liner designed to offer excellent die cutting and label dispensing.

Tensile lbs/in MD 19,000 / CD 23,000

Caliper: .00142" +/- 10% Basis Weight 31#

ADHESIVE

HP1+ adhesive is a high tack, high performance hot melt rubber based adhesive engineered to provide high adhesion while maintaining resistance to severe environments including exposure to petroleum based oils, grease, organic solvents and high humidity. HP1 also provides a high level of performance on LSE plastics including HDPE and adheres well to powder coated surfaces.

Caliper: 0.0018" +/-10%
Soft: 195°F

Min. Application Temperature: 40°F
Service Temperature Range: -40° to 200° F

Release Liner

A 50# moisture stabilized 3.1mil bleach super calendered kraft paper stock, offering excellent die cutting and matrix stripping.

Caliper: .0031" +/- 10%

Basis Weight: 50#

CONSTRUCTION CALIPER

.00912" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com