



# Performance Guide

Represents Typical Values Only

**3Mil Matte White Polypropylene TT CrocLock HCW 40#**

**Item: C1011**

## FACE

3Mil White Film, mineral-filled, biaxially oriented polypropylene is designed for applications requiring strength and durability. A matte print receptive coating is specifically designed for excellent thermal transfer printability.

Caliper: .003" +/- 10%

## ADHESIVE

CrocLock is an aggressive hot melt adhesive designed for difficult to label substrates. Key attributes include excellent on press convertibility as well as quick tack properties. Designed for use on wood, texture surfaces, plastics, corrugated and other hard to label surfaces.

Caliper: 0.0012

Min. Application Temperature: 30°F

Service Temperature Range: -40° to +145° F

Loop Tack ATSM D-6195

Stainless steel #/inch: 6lbs

Peel Adhesion 180 10 minutes /

24 hours / lbs per lineal inch:

| Stainless | HDPE    | Corrugated | Wood    | Powder Coat |
|-----------|---------|------------|---------|-------------|
| 6.5/6.7   | 4.0/4.5 | 3.5/4.0    | 3.5/4.0 | 6.5/6.5     |

Shear : 3100

ASTM D-3654 Shear (minutes) 1" X 1" X 1000 grams



## LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%

Basis Weight: 40#

## CONSTRUCTION CALIPER

.0066" +/- 10%

**Shelf life: 1 year stored at 72°F and 50% RH**

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

**Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839**

**800-813-8907**

[www.paperresources.com](http://www.paperresources.com)