



Performance Guide

Represents Typical Values Only

2Mil Clear Polypropylene TC CrocLock HCW 40#

Item # C1018

FACE

A 2mil transparent, top coated, biaxially oriented polypropylene film.

Caliper: .002" +/- 10%	Elongation % MD: 180
Basis Weight: 28.8lbs/ream	Elongation % CD: 55
Surface Tension: 42	Tensile MD: 20,000psi
	Tensile CD: 35,000psi

ADHESIVE

CrocLock E is an aggressive hot melt adhesive designed for difficult to label surfaces. This adhesive has excellent tack and peel properties at a wide range of temperatures. Excellent adhesion to corrugated and other packaging materials when moisture, dirt and debris may be present on the application surface.

Caliper: 0.0014

Service Temperature Range: -50° to +185° F

Loop Tack ATSM D-6195 Stainless

steel #/inch: 6.8lbs

Peel Adhesion 180 10 minutes / 24 hours / lbs per lineal inch:	Stainless	HDPE	Corrugated	Wood	Powder Coat
	6.5/6.7	4.0/4.5	3.5/4.0	3.5/4.0	6.5/6.5

Shear : 3100 ASTM D-3654 Shear (minutes) 1" X 1" X 1000 grams

Minimum application temperature: 30°F



LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%
Basis Weight: 40#

CONSTRUCTION CALIPER

.0059" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com