



# Performance Guide

Represents Typical Values Only

**2Mil Brushed Silver PET TC SnappLock 50#**

**Item # C1062**

## FACE

2mil Brushed Silver Polyester topcoated for flexographic and thermal transfer printing. Decorative Brushed PET offers excellent tear strength, heat resistance, dimensional stability, high opacity and chemical resistance.

Caliper: .002" +/- 10%  
Weight: n/a

Tensile MD: 26,000psi Basis  
Tensile CD: 35,000psi

## ADHESIVE

SnappLock is an aggressive hot melt adhesive featuring high initial tack and SAFT. This adhesive is an excellent die cutting adhesive that will maximize press speeds and still offer high initial tack. Designed for use on plastic, corrugated and stainless steel and other difficult to label substrates.

Caliper: 0.001+  
Min. Application Temperature: 40°F  
Service Temperature Range: -40° to +190° F

Loop Tack Stainless Steel (lbf)	11.3				
Peel Adhesion 180 10 minutes /	<b>Stainless</b>	<b>HDPE</b>	<b>Corrugated</b>	<b>Wood</b>	<b>Powder Coat</b>
24 hours / lbs per lineal inch:	6.7/7.3	5.4/6.9	n/a	.9/.9	n/a
Shear :	n/a				
180 Peel:	7.2				

## LINER

A 50# liner (3.1mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0031" +/- 10%  
Basis Weight: 50#

## CONSTRUCTION CALIPER

.0061" +/- 10%

**Shelf life: 1 year stored at 72°F and 50% RH**

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

**Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839**

**800-813-8907**

[www.paperresources.com](http://www.paperresources.com)