



Performance Guide

Represents Typical Values Only

3.2Mil Matte White PP TIRE 50#

Item # C1171

FACE

3.2Mil White Film, mineral-filled, biaxially oriented polypropylene is designed for applications requiring strength and durability. This film is clay coated both sides for excellent thermal transfer printing and enhanced adhesive anchorage.

Caliper: .0032" +/- 10%

Opacity: 89%

Tensile Strength psi: 13,000 MD

Tensile Strength psi: 20,000 TD

ADHESIVE

Tire label adhesive is an aggressive hot melt rubber based adhesive designed for hard to label substrates such as tires, recycled corrugated packaging, fabrics and other rough surfaces.

Caliper: 0.002

Min. Application Temperature: 10°F

Service Temperature Range: -60° to +145° F

Loop Tack: 126 oz/in sq

LINER

50# silicone coated release liner designed for high speed label converting. Excellent for roll-to-roll label applications.

Caliper: .0031" +/- 10%

Basis Weight: 50#

CONSTRUCTION CALIPER .0083" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com