



Performance Guide

Represents Typical Values Only

3MIL Matte WHT PP CrocLock E HCWT 40#

Item # C1224

FACE

3Mil White Film, mineral-filled, biaxially oriented polypropylene is designed for applications requiring strength and durability. A matte print receptive coating is specifically designed for excellent thermal transfer printability.

Caliper: .003" +/- 10%

ADHESIVE

CrocLock E is an aggressive hot melt adhesive designed for difficult to label surfaces. This adhesive has excellent tack and peel properties at a wide range of temperatures. Excellent adhesion to corrugated and other packaging materials when moisture, dirt and debris may be present on the application surface.

Caliper: 0.0012" +/-10%

Min. Application Temperature: 30F

Service Temperature Range: -50° - +185° F

Loop Tack: 6.8lbs

Peel: 5.8lbs

SAFT: 165

LINER

A 40# liner (2.4mil) bleached, super calendered kraft liner featuring excellent die cutting and matrix stripping.

Caliper: .0024" +/- 10%

Basis Weight: 40#

CONSTRUCTION CALIPER

.0065" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com